



Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	M12 plunger head
Product compatibility	XCKP XCMD XCKD XCKT
Associated body	ZCMD21L08R12 ZCMD81L1 ZCMD39L5 ZCMD21M12 ZCMD41L1 ZCMD69C12 ZCMD81L2 ZCMD81L5 ZCMD29C12 ZCMD39L1 ZCMD39L2 ZCMD61C12 ZCMD21L5 ZCMD29L5 ZCMD41L5 ZCMD37L2 ZCMD29L1 ZCMD37L1 ZCMD61M12 ZCMD21L1 ZCMD21C12 ZCMD21L08U78 ZCMD37L5 ZCMD25L2 ZCMD29L2 ZCMD21L2 ZCMD25L1 ZCMD25L5 ZCMD41L2
Movement of operating head	Linear
Type of operator	End plunger spring return metal
Type of approach	Vertical approach 1 direction

Complementary

Positive opening	With
------------------	------

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0851 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------