

# ZCKJ1121H29

Limit switch body, Limit switches XC Standard, ZCKJ, plug in, with display, 1C/O, snap action, M20



## Main

|                               |  |
|-------------------------------|--|
| Range of product              | Telemecanique Limit switches XC Standard   |
| Series name                   | Standard format  |
| Product or component type     | Limit switch body  |
| Device short name             | ZCKJ   |
| Body type                     | Plug-in body   |
| Product compatibility         | XCKJ   |
| Associated head               | ZCKE23<br>ZCKE05<br>ZCKE21<br>ZCKE67<br>ZCKE619<br>ZCKE62<br>ZCKE66<br>ZCKE63<br>ZCKE06<br>ZCKE61<br>ZCKE65<br>ZCKE64<br>ZCKE08<br>ZCKE629 |
| Body material                 | Metal  |
| Cable entry                   | 1 entry tapped for M20 x 1.5 cable gland   |
| Number of poles               | 1  |
| Contacts type and composition | 1 C/O  |
| Contact operation             | Snap action  |
| Number of steps               | 1 1 position   |
| Contacts material             | Silver plated contacts   |

## Complementary

|  |   |
|--|---|
| Local display                                | With  |
| Electrical connection                        | Screw-clamp terminals, clamping capacity: 1 x 0.75...2 x 1.5 mm <sup>2</sup>  |
| Positive opening                             | Without   |
| Minimum actuation speed                      | 0.01 m/min  |
| [Ie] rated operational current               | 3 A at 240 V, AC-15, A300 conforming to EN/IEC 60947-5-1 appendix A<br>0.27 A at 250 V, DC-13, Q300 conforming to EN/IEC 60947-5-1 appendix A   |
| [Ithe] conventional enclosed thermal current | 10 A  |
| [Ui] rated insulation voltage                | 500 V (pollution degree 3) conforming to IEC 60947-1 for contact block<br>300 V conforming to CSA C22.2 No 14 for contact block<br>300 V conforming to UL 508 for contact block<br>50 V conforming to IEC 60947-1 for indicator light module  |
| Maximum resistance across terminals          | 0.25 mOhm conforming to IEC 60255-7 category 3  |
| [Uimp] rated impulse withstand voltage       | 6 kV conforming to IEC 60664<br>6 kV conforming to IEC 60947-1  |
| Short-circuit protection                     | 10 A cartridge fuse, type gG  |
| Electrical durability                        | 5000000 Cycles, DC-13 120 V, 4 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 Cycles, DC-13 24 V, 10 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13 48 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                               |   |
|-------------------------------|---|
| Electrical circuit type       | Indicator light module 2 LED DC, 24 V (20...30 V) service life: 100000 h with reverse polarity protection |
| Width                         | 43 mm   |
| Height                        | 84 mm   |
| Depth                         | 36 mm   |
| Net weight                    | 0.3 kg  |
| Terminals description ISO n°1 | (11-12)NC<br>(13-14)NO  |

## Environment

|                                       |                                  |
|---------------------------------------|----------------------------------|
| IP degree of protection               | IP66                             |
| IK degree of protection               | IK07                             |
| Ambient air temperature for operation | 10...120 °C for high temperature |
| Ambient air temperature for storage   | 10...120 °C                      |
| Environmental characteristic          | High temperature                 |

## Packing Units

|                              |     |
|------------------------------|-----|
| Unit Type of Package 1       | PCE |
| Number of Units in Package 1 | 1   |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product  |
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|