



Part Number : [1301500146](#)

Product Description : 20 Amp Watertite Pin and Sleeve Receptacle with Flip Lid, 3 Pole/4 Wire, 3ø 600V, Black

Series Number : 130150

Status : Active

Product Category : Wiring Devices

Engineering Number : 420R5W



Documents & Resources

Drawings

[1301500146_sd.pdf](#)

Product Environment Compliance

Compliance

| | |
|--------------------|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | Not Reviewed per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21 |
| REACH SVHC | Not Reviewed per D(2024)6225-DC (07 Nov 2024) |
| EU RoHS | Not Reviewed per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Part Details

General

| | |
|--------------------|---|
| Status | Active |
| Category | Wiring Devices |
| Series | 130150 |
| Description | 20 Amp Watertite Pin and Sleeve Receptacle with Flip Lid, 3 Pole/4 Wire, 3ø 600V, Black |
| Comments | IEC Configuration 309-1/309-2 |
| IP Rating | IP67 |
| NEMA Configuration | N/A |
| Product Name | Watertite |
| Specialty | Pin and Sleeve |
| Type | Receptacle |
| UPC | 78678870334 |

Agency

| | |
|----|---------|
| UL | E145923 |
|----|---------|

Electrical

| | |
|-------------------------------|---------|
| Current - Maximum per Contact | 20.0A |
| GFCI | No |
| Voltage - Maximum | 3Ø 600V |

Physical

| | |
|-------------------|---------------|
| Cord Type | N/A |
| Flange | Yes |
| Flip Lid | Yes |
| Gender | Female |
| Length | N/A |
| Lighted Connector | No |
| Locking Blade | Yes |
| Poles | 3-pole/4-wire |

| | |
|-----------------|--------|
| Receptacle Type | Single |
|-----------------|--------|

This document was generated on Feb 09, 2025