



**Part Number :** [2214423241](#)

**Product Description :** Mini-Fit TPA2/Sigma Female Low Mating Force Crimp Terminal, Copper Alloy, Post-Plated Tin (Sn), 20-18 AWG, 1.42-2.10mm Insulation Diameter, Reel

**Series Number :** 221442

**Status :** Active

**Product Category :** Crimp Terminals



---

## Documents and Resources

### Drawings

[2214423241 sd.pdf](#)

[2214420000-PK-000.pdf](#)

[STEP AP242](#)

[SOLIDWORKS](#)

[Creo](#)

### Specifications

[PS-172718-0000-001.pdf](#)

[2131370000-PS-000.pdf](#)


[1727180001-TS-000.pdf](#)

[2131370001-TS-000.pdf](#)

---

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	 per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2025)6375-DC (05 Nov 2025)
EU RoHS	Compliant per EU 2015/863

## Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

## Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## Substances of Interest

- PFAS

## EU RoHS Certificate of Compliance

## Additional Product Compliance Information

---

## Part Details

### General

Status	Active
Category	Crimp Terminals
Series	221442
Description	Mini-Fit TPA2/Sigma Female Low Mating Force Crimp Terminal, Copper Alloy, Post-Plated Tin (Sn), 20-18 AWG, 1.42-2.10mm Insulation Diameter, Reel
Application	Power, Wire-to-Wire, Wire-to-Board
Product Name	Mini-Fit Sigma,Mini-Fit TPA2
UPC	198282439219

### Electrical

Current - Maximum per Contact	10.0A
Voltage - Maximum	600V AC/DC

### Physical

Durability (mating cycles max)	30
Gender	Female
Material - Metal	Copper Alloy

Material - Plating Mating	Tin
Material - Plating Termination	Tin
Net Weight	0.182/g
Packaging Type	Reel
Plating min - Mating	1.250µm
Plating min - Termination	2.500µm
Termination Interface Style	Crimp or Compression
Wire Insulation Diameter	1.42-2.10mm
Wire Size (AWG)	18, 20
Wire Size mm <sup>2</sup>	N/A

## Mates With / Use With

### Use with Part(s)

Description	Part Number
Mini-Fit TPA2 and Mini-Fit Sigma Dual Row Receptacle Housings	<a href="#"><u>172708</u></a>
Mini-Fit TPA2 and Mini-Fit Sigma Single Row Receptacle Housings	<a href="#"><u>200453</u></a>

---

## Application Tooling

### Global

Description	Part Number
FineAdjust Applicator for Mini-Fit TPA2 Crimp Terminals, 0.50mm <sup>2</sup> , 0.75mm <sup>2</sup> and 20-18 AWG wires	<a href="#"><u>639036900</u></a>
Hand Crimp Tool for Mini-Fit TPA2 Male and Female Crimp Terminals, 20 AWG, Large and Small Insulation Grips	<a href="#"><u>2002182100</u></a>
Hand Crimp Tool for Mini-Fit TPA2 Male and Female Crimp Terminals, 18 AWG, Large and Small Insulation Grips	<a href="#"><u>2002180100</u></a>