

CARRIER/L-EMP (1000X15) TR - Marker carriers



0829560

<https://www.phoenixcontact.com/nl/products/0829560>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Profile, self-adhesive, 1000 mm long, for accommodating UC-,/US-, LS-, and EMT (EX15)R material, 15 mm height

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 0829560 |
| Packing unit | 25 pc |
| Minimum order quantity | 25 pc |
| Sales key | BG241A |
| Product key | BG241A |
| GTIN | 4046356614917 |
| Weight per piece (including packing) | 27,5 g |
| Weight per piece (excluding packing) | 27,5 g |
| Customs tariff number | 39162000 |
| Country of origin | DE |

CARRIER/L-EMP (1000X15) TR - Marker carriers



0829560

<https://www.phoenixcontact.com/nl/products/0829560>

Technical data

Dimensions

| | |
|--------|---------|
| Width | 1000 mm |
| Height | 17.6 mm |
| Depth | 6.6 mm |

Text field

| | |
|-------------------|---------|
| Text field width | 1000 mm |
| Text field height | 15 mm |

Material specifications

| | |
|-----------------------|---------------|
| RoHS compliant | yes |
| Adhesive | Acrylic |
| Color | transparent |
| Material | PVC |
| Base element material | PVC |
| Components | Silicone-free |

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

| | |
|---|----------------------|
| Testing for paint wetting impairment substances (LABS-conformity) | VW PV 3.10.7:2005-02 |
| Result | Test passed |

UV resistance

| | |
|---------------|---------------------------------------|
| Specification | DIN EN ISO 4892-2:2021-11 (following) |
| Result | Test passed |
| Test duration | 96 h |
| Procedure | Artificial irradiation. |

Temperature storage

| | |
|---------------------|-----------------------|
| Specification | IEC 60068-2-2:2007-07 |
| Result | Test passed |
| Procedure | Test Bb |
| Duration | 96 h |
| Maximum temperature | +60 °C |

Testing in a condensation changing climate in the presence of sulfur dioxide

| | |
|---------------|--------------------------|
| Specification | DIN EN ISO 22479:2022-08 |
| Result | Test passed |
| Procedure | Method B |
| Cycles | 2 |

Salt spray test

CARRIER/L-EMP (1000X15) TR - Marker carriers



0829560

<https://www.phoenixcontact.com/nl/products/0829560>

| | |
|---------------|---|
| Specification | DIN EN IEC 60068-2-11 (VDE 0468-2-11):2022-10 |
| Result | Test passed |

Mounting

| | |
|---------------|----------|
| Mounting type | adhesive |
|---------------|----------|

CARRIER/L-EMP (1000X15) TR - Marker carriers



0829560

<https://www.phoenixcontact.com/nl/products/0829560>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 27281105 |
| ECLASS-15.0 | 27281105 |

ETIM

| | |
|-----------|----------|
| ETIM 10.0 | EC002248 |
|-----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

CARRIER/L-EMP (1000X15) TR - Marker carriers



0829560

<https://www.phoenixcontact.com/nl/products/0829560>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

EF3.1 Climate Change

| | |
|---------|---------------|
| CO2e kg | 0,495 kg CO2e |
|---------|---------------|

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT B.V.
Hengelder 56 6902 PA Zevenaar
Postbus 246 6900 AE Zevenaar
(0316) 59 17 20
sales@phoenixcontact.nl