

BL2 PPC 1200 - Panel PC



1138377

<https://www.phoenixcontact.com/nl/products/1138377>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Image shows 10-inch display

IP65 panel PC (PPC) with 7- or 10-inch screen, Intel® Celeron® N3350 processor, 4 GB of RAM, choice of mSATA SSD, and available with Windows 10 IoT Enterprise LTSC 2019 operating system.

Commercial data

Item number	1138377
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	DRBABB
Product key	DRBABB
Weight per piece (including packing)	100 g
Weight per piece (excluding packing)	100 g
Customs tariff number	84714100
Country of origin	TW

Technical data

Notes

Note on application

Note on application	Only for industrial use
---------------------	-------------------------

Product properties

Computer data

Processor	Intel® Celeron® N3350
Operating system	Windows® 10 IoT Enterprise LTSC 2019 (64-bit), Multi-language without operating system
RAM	4 GB DDR3 SODIMM
Data storage system	configurable
Cooling	passive

Display

Display type	17.8 cm / 7"-TFT
	25.7 cm / 10.1"-TFT
Screen resolution	1024 x 600 Pixel(s) (WVGA), 7" TFT
	1280 x 800 Pixel(s) (WVGA), 10-inch TFT
Touch technology	projective-capacitive (PCAP)
Display lighting type	LED
Brightness	300 cd/m ² , typical (adjustable)
MTBF	> (Screen dependent)
Reading angle bottom	Both 7" and 10.1" are 10-point touch

System properties

User software	without user software
	Visu+

Electrical properties

Service life of battery	5 years (typical)
-------------------------	-------------------

Supply

Power supply unit	24 V DC ±20 %
Max. current consumption	configuration dependent

Real-time clock

Realtime clock	Yes (battery-backed)
----------------	----------------------

Connection data

Connection method	Screw connection
Conductor cross-section, rigid	0.14 mm ² ... 1.5 mm ²
Conductor cross-section, flexible	0.14 mm ² ... 1.5 mm ²

Conductor cross-section AWG	28 ... 16
Stripping length	7 mm

Interfaces

Interfaces	1x COM (RS-232)
	1x USB 2.0
	2x USB 3.0
Optional interfaces	2x COM (RS-232/422/485)
Monitor output	1x HDMI
Network	2x Ethernet (10/100/1000 Mbps), RJ45
LAN chipset	Intel® I210-AT

Dimensions

External dimensions

Width / Height / Depth	196 mm / 134 mm / 48 mm (7-inch display)
	266 mm / 184 mm / 48 mm (10-inch display)

Installation dimensions

Width / Height / Installation depth	186 mm / 124 mm / (Panel cutout for 7" display)
	229 mm / 155 mm / (Panel cutout for 10" display)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	-5 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Permissible humidity (operation)	10 % ... 90 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 90 % (non-condensing)
Shock	20g, 11 ms in accordance with IEC 60068-2-27
Vibration (operation)	DIN EN 60068-2-6

Mounting

Mounting type	Front mounting
	VESA holder (not for industrial use)
Holder system	VESA MIS-D 75
	VESA MIS-D 100 C

BL2 PPC 1200 - Panel PC



1138377

<https://www.phoenixcontact.com/nl/products/1138377>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/nl/products/1138377>



IECEE CB Scheme

Approval ID: US-36011-UL



cULus Listed

Approval ID: E238705

BL2 PPC 1200 - Panel PC



1138377

<https://www.phoenixcontact.com/nl/products/1138377>

Classifications

ECLASS

ECLASS-13.0	19200103
ECLASS-15.0	19200103

ETIM

ETIM 9.0	EC001414
----------	----------

UNSPSC

UNSPSC 21.0	43211500
-------------	----------

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c), 7(a), 7(c)-I

China RoHS

Environment friendly use period (EFUP)	EFUP-10
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	1, 2-dimethoxyethane; ethylene glycol dimethyl ether (EGDME)(CAS: 110-71-4)
	Lead titanium trioxide(CAS: 12060-00-3)
	Lead(CAS: 7439-92-1)

EF3.1 Climate Change

CO2e kg	3,387 kg CO2e
---------	---------------