

1-1415060-1 ✓ ACTIVE

SCHRACK | SCHRACK SR6

TE Internal #: 1-1415060-1

Force-Guided Relay, AC, Monostable, 3A (NO) + 3B (NC), 8 A  
Contact Rating, 230 VAC Coil Voltage, 250 VAC Contact Voltage,  
DIN Rail, SCHRACK SR6

[View on TE.com >](#)



Relays & Contactors > Electromechanical Relays > Force Guided Relay, DIN-rail



Relay & Contactor Type: **Force-Guided Relay**

Coil Magnetic System: **Monostable**

Contact Arrangement: **3A (NO) + 3B (NC)**

Current Type: **AC**

Contact Current Rating: **8 A**

[All Force Guided Relay, DIN-rail \(8\)](#)

## Features

### Product Type Features

Relay & Contactor Type	Force-Guided Relay
------------------------	--------------------

### Configuration Features

Contact Number of Poles	6
Coil Special Features	Diode Rectified
Contact Arrangement	3A (NO) + 3B (NC)

### Electrical Characteristics

Contact Limiting Short-Time Current	8 A
Contact Limiting Making Current	8 A
Contact Limiting Continuous Current	8 A
Contact Limiting Breaking Current	8 A
Insulation Initial Dielectric Between Open Contacts	1000 Vrms
Insulation Initial Dielectric Between Adjacent Contacts	2000 Vrms
Contact Switching Voltage (Max)	250 VAC
Contact Switching Load (Min)	10mA @ 5V
Coil Resistance	10080 $\Omega$
Coil Power Rating AC	2.4 VA
Contact Current Rating	8 A



Coil Voltage Rating	230 VAC
Contact Voltage Rating	250 VAC
Insulation Initial Dielectric Between Contacts & Coil	3000 Vrms

### Body Features

Product Weight	90 g[3.175 oz]
Enclosure Type	Dust Protected

### Contact Features

Contact Material	AgSnO2
------------------	--------

### Termination Features

Main Termination & Connection Type	Connector
Coil Termination & Connection Type	Connector

### Mechanical Attachment

Product Mount Type	DIN Rail
--------------------	----------

### Dimensions

Insulation Clearance Between Contact & Coil	5.5 mm[.217 in]
Insulation Creepage Between Contact & Coil	5.5 mm[.217 in]
Product Width	46 mm[1.81 in]
Product Length	87 mm[3.425 in]
Product Height	66.5 mm[2.61 in]

### Usage Conditions

Operating Temperature Range	-25 – 50 °C[-13 – 122 °F]
Environmental Category of Protection	RTI
Environmental Ambient Temperature (Max)	50 °C[122 °F]

### Operation/Application

Coil Magnetic System	Monostable
Current Type	AC

### Product Availability

Product Availability	Worldwide
----------------------	-----------

### Packaging Features

Packaging Method	Box & Carton
------------------	--------------

### Other



	>1.8 – ≤2.5 VA
Contact Current Class	>5 – ≤10 A
Height Class (Mechanical)	>45 – ≤70 mm[>1.772 – ≤2.756 in]
Length Class (Mechanical)	>70 mm[>2.756 in]
Width Class (Mechanical)	>33 mm[>1.299 in]

## Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Also in the Series | **SCHRACK SR6**



AC Relays(4)



PCB Relays(75)

## Customers Also Bought

TE Part #228226-1  
BNC BLKHD JACK ADAPTER GOLDTE Part #350687-7  
UMNL SPLIT PIN AUNI/BRTE Part #770988-3  
MINI UMNL SOK 22-18AWG AU LPTE Part #1-794610-2  
MICRO MNL RPT CNT,LS PC 30AU LTE Part #4-1393117-3  
KUP-11D15-110=KUTE Part #CAT-SCH691-SR1D  
Force Guided Relay, DIN-railTE Part #9-1437624-6  
PKS1105B101/4=0-10 1/4 PKS-770TE Part #2-2176308-7  
RP 1E 0.1W 249K 0.1% 25PPM 5K RLTE Part #1-6609035-4  
30ESK6=F7517 S0

## Documents

### CAD Files

[3D PDF](#)

[3D](#)

### Customer View Model

[ENG\\_CVM\\_CVM\\_1-1415060-1\\_C.2d\\_dxf.zip](#)

English

### Customer View Model

[ENG\\_CVM\\_CVM\\_1-1415060-1\\_C.3d\\_igs.zip](#)



English

### Customer View Model

[ENG\\_CVM\\_CVM\\_1-1415060-1\\_C.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

---

### Datasheets & Catalog Pages

[Safety Relay Module SR6Z](#)

English

---

### Product Specifications

[Definitions General Purpose Relays](#)

English

---

### Agency Approvals

[CE Declaration of Conformity](#)

English