



TE Internal #: 2326768-2
 Connector Kit, Receptacle, Crimp, Wire-to-Motor, Gold, Normal,
 UL 94V-0, 4 Position, 4.6 mm [.181 in] Centerline, Standard
 Rectangular Connectors

[View on TE.com >](#)

Connectors > Rectangular Connectors > Standard Rectangular Connectors



Connector Product Type: **Connector Kit**
 Connector & Housing Type: **Receptacle**
 Mating Retention: **With**
 Mating Retention Type: **Screwlocks**
 Termination Method to Wire & Cable: **Crimp**

Features

Body Features

Seal Type	Panel Gasket
-----------	--------------

Dimensions

Row-to-Row Spacing	4.6 mm [.181 in]
--------------------	------------------

Configuration Features

Number of Loaded Positions	4
Number of Positions	4
Number of Rows	2

Contact Features

Contact Underplating Material	Nickel
Wire Contact Termination Area Plating Material	Nickel
Contact Mating Area Plating Material	Gold
Contact Retention Within Housing	With
Contact Current Rating (Max)	7 A

Product Type Features



Connector Product Type	Connector Kit
Connector & Housing Type	Receptacle
Connector System	Wire-to-Motor
Insertion Force Type	Normal
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable

Mechanical Attachment

Mating Retention	With
Mating Retention Type	Screwlocks
Connector Mounting Type	Cable Mount (Free-Hanging)

Termination Features

Termination Method to Wire & Cable	Crimp
------------------------------------	-------

Electrical Characteristics

Operating Voltage	370 VAC
-------------------	---------

Housing Features

Centerline (Pitch)	4.6 mm [.181 in]
--------------------	------------------

Usage Conditions

Operating Temperature Range	-30 – 105 °C [-22 – 221 °F]
-----------------------------	-----------------------------

Operation/Application

Shielded	No
Circuit Application	Power

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Other

EU RoHS Compliance	Compliant
EU ELV Compliance	Compliant

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold



EU REACH Regulation (EC) No. 1907/2006

Current ECHA Candidate List: JUNE 2024 (241)

Candidate List Declared Against: JUNE 2024 (241)

Does not contain REACH SVHC

Halogen Content

Not Low Halogen - contains Br or Cl > 900 ppm.

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2261091-6
RECEPTACLE CONTACT 4POS.,MMC-PUSH ON-P-F

TE Part # 2255334-1
SDE12 HAND TOOL FOR MMC PUSH ON P-F REC.

Customers Also Bought



TE Part #CAT-D9934-A15B
Receptacle and Tab Housing: 2.5 mm Pitch, 250V



TE Part #CAT-D9934-A75B
Receptacle and Tab Housing: 5.08 mm Pitch, 250-600V



TE Part #1-1318119-4
DYNAMIC D-2100 REC HSG 8P



TE Part #2304873-2
KIT, REC CONN,WITH CONT, MMC-PUSH ON-B-F



Documents

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_2326768-2_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2326768-2_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2326768-2_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English