

3-173983-5 ✓ ACTIVE

AMP-IN

TE Internal #: 3-173983-5

Board-In PCB Mount One-Piece IDC Connector, Horizontal, Wire-to-Board, 15 Position, 2 mm [.079 in] Centerline, Discrete Wire, Through Hole - Solder

[View on TE.com >](#)



Connectors > PCB Connectors > Board-In Connectors



PCB Connector Assembly Type: **PCB Mount One-Piece IDC Connector**

PCB Mount Orientation: **Horizontal**

Connector System: **Wire-to-Board**

Number of Positions: **15**

Centerline (Pitch): **2 mm [.079 in]**

Features

Electrical Characteristics

Operating Voltage	125 VDC
-------------------	---------

Industry Standards

UL Flammability Rating	UL 94V-0
Compatible With Approved Standards Products	UL E28476, CSA LR7189

Dimensions

PCB Thickness (Recommended)	.8 mm[.031 – .063 in]
Connector Height	4 mm[.157 in]
Connector Length	32 mm[1.26 in]

Packaging Features

Packaging Quantity	90
Packaging Method	Tray, Box

Operation/Application

Assembly Process Feature	Pick and Place Cover
Circuit Application	Signal

Contact Features

Contact Shape & Form	Tuning Fork
Contact Layout	Inline
Contact Base Material	Phosphor Bronze



PCB Contact Termination Area Plating Material	Pre-Tin
-----------------------------------------------	---------

Contact Current Rating (Max)	2 A
------------------------------	-----

Mechanical Attachment

PCB Mount Retention Type	Kinked Legs
--------------------------	-------------

PCB Mount Alignment Type	Polarized Lock
--------------------------	----------------

PCB Mount Alignment	Without
---------------------	---------

PCB Mount Retention	With
---------------------	------

Termination Features

Termination Post & Tail Length	3.5 mm[.138 in]
--------------------------------	-----------------

Termination Method to PCB	Through Hole - Solder
---------------------------	-----------------------

Product Type Features

PCB Connector Assembly Type	PCB Mount One-Piece IDC Connector
-----------------------------	-----------------------------------

Connector System	Wire-to-Board
------------------	---------------

Connector & Contact Terminates To	Printed Circuit Board, Wire & Cable
-----------------------------------	-------------------------------------

Configuration Features

PCB Mount Orientation	Horizontal
-----------------------	------------

Number of Positions	15
---------------------	----

Compatible With Wire & Cable Type	Discrete Wire
-----------------------------------	---------------

Number of Rows	1
----------------	---

Body Features

Primary Product Color	Cream Yellow
-----------------------	--------------

Housing Features

Centerline (Pitch)	2 mm[.079 in]
--------------------	---------------

Housing Material	PBT GF
------------------	--------

Usage Conditions

Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]
-----------------------------	----------------------------

Other

EU RoHS Compliance	Compliant
--------------------	-----------

EU ELV Compliance	Compliant
-------------------	-----------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



Customers Also Bought





Documents

Product Drawings

[AMP CT MT AMP-IN HDR-H YEL 15P](#)

English

CAD Files

[3D PDF](#)

English

Customer View Model

[ENG_CVM_3-173983-5_F.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_3-173983-5_F.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_3-173983-5_F.2d_dxf.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Application Specification](#)

English

Instruction Sheets

[MINI PRESS CT CONNECTOR \(WAS IS-553J\)](#)

Japanese

[Instruction Sheet \(non U.S.\)](#)

Japanese