MTA 45 MF

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com



Due to the wide range of variants with output voltages of 5, 12, 24, and 48 V and extensive international approvals, they are suitable for use in many applications. The power range extends from 35 W to 350 W. The individual adaptability makes PRO-PM the right choice for many standard machines.

General ordering data

Version	Electronics housings, Mounting flange
Order No.	1251310000
Type	MTA 45 MF
GTIN (EAN)	4050118042719
Qty.	1 pc(s).

MTA 45 MF

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Dimensions and weights

Height	10.5 mm	Height (inches)	0.413 inch
Width	47 mm	Width (inches)	1.85 inch
Length	97.3 mm	Length (inches)	3.831 inch
Net weight	97 g		

General data

Protection degree	IP20	Weight	97 g

Classifications

ETIM 6.0	EC002625	ETIM 7.0	EC002625
ETIM 8.0	EC002625	ECLASS 9.0	27-18-28-07
ECLASS 9.1	27-04-92-90	ECLASS 10.0	27-18-28-07
ECLASS 11.0	27-18-28-07	ECLASS 12.0	27-18-28-07

Approvals

ROHS	Conform

Downloads

Engineering Data	CAD data – STEP
Engineering Data	WSCAD
Catalogues	Catalogues in PDF-format
Brochures	